



A Division of World Industrial Equipment, Inc.
"Designer & Manufacturer of Lift Equipment"



SIGNALIER

ATR 52-58

Articulated/Telescopic Aerial Lift



4850 ORANGE AVENUE • FORT PIERCE, FL 34947
(772) 461-6056 MAIN PLANT • 1-800-226-5056 IN FLORIDA • (772) 464-2716 FAX
www.stamm-mfg.com • Email: johnnystm@stamm-mfg.com



SIGNALIER

ATR 52-58



GENERAL SPECIFICATIONS

(Based on 40" Frame)

	ATR-52	ATR-58
Horizontal Reach	30'-9" (9.4 m)	30'-4" (9.2 m)
Max Platform Capacity	500 lbs (227 kg)	500 lbs (227 kg)
Platform Rotation	180°	180°
Max Jib Capacity	1000 lbs (454 kg)	1000 lbs (454 kg)

HEIGHTS WITH STANDARD PEDESTAL

	ATR-52	ATR-58
Bottom of Platform Height	46'-4" (14.1 m)	50'-6" (15.4 m)
Working Height	51'-4" (15.6 m)	55'-6" (16.9 m)
Stowed Travel Height	10'-6" (3.2 m)	10'-6" (3.2 m)

BOOM ACTION

	ATR-52	ATR-58
Outer/Inner Boom Articulation	-25 to + 85°	-25 to + 85°
Inner Boom Extension	103" (2.6 m)	53" (1.35 m)
Lower Boom Articulation	0 to 84°	0 to 84°
Rotation	360°	360°

INSULATION (where applicable)

	ATR-52	ATR-58
Upper Boom Insulation Gap	64" (1.6 m)	64" (1.6 m)
Lower Boom Insulation Gap	12" (305 mm)	12" (305 mm)

VEHICLE REQUIREMENTS

	ATR-52	ATR-58
Cab to Axle (minimum)	84" (2.14 m)	102" (2.6 m)
GVWR	17,500 lbs (7,940 kg)	24,000 lbs (10,890 kg)

4850 ORANGE AVENUE • FORT PIERCE, FL 34947
 (772) 461-6056 MAIN PLANT • 1-800-226-5056 IN FLORIDA • (772) 464-2716 FAX
 www.stamm-mfg.com • Email: johnnystm@stamm-mfg.com