



**VO-350/355/360-MHI**  
**VO-350-X/355-X/360-X-MHI**

**DEMAND BETTER**







# VO-350/355/360-MHI VO-350-X/355-X/360-X-MHI

## GENERAL SPECIFICATIONS

	VO-350	VO-350-X	VO-355	VO-355-X	VO-360	VO-360-X
Height to Bottom of Platform	50.3' (15.3 m)	50.3' (15.3 m)	55.3' (16.9 m)	55.3' (16.9 m)	60.3' (18.4 m)	60.3' (18.4 m)
Working Height	55.3' (16.9 m)	55.3' (16.9 m)	60.3' (18.4 m)	60.3' (18.4 m)	65.3' (19.9 m)	65.3' (19.9 m)
Horizontal Reach Overcenter	42.2' (12.9 m)	42.2' (12.9 m)	47.2' (14.4 m)	47.2' (14.4 m)	52.2' (15.9 m)	52.2' (15.9 m)
Horizontal Reach Non-Overcenter	31.9' (9.7 m)	39.2' (11.9 m)	34.9' (10.6 m)	43.2' (13.2 m)	37.9' (11.6 m)	47.1' (14.4 m)
Max Platform Capacity Single 1-Man	450 lbs (205 kg)	450 lbs (205 kg)	450 lbs (205 kg)	450 lbs (205 kg)	450 lbs (205 kg)	450 lbs (205 kg)
Max Platform Capacity Single 2-Man	800 lbs (360 kg)	800 lbs (360 kg)	800 lbs (360 kg)	800 lbs (360 kg)	600 lbs (270 kg)	600 lbs (270 kg)
Max Total Platform Capacity Dual 1-Man	800 lbs (360 kg)	800 lbs (360 kg)	800 lbs (360 kg)	800 lbs (360 kg)	Not available	Not Available
Max Total Platform Capacity Dual 1-Man With Dual Controls	800 lbs (360 kg)	800 lbs (360 kg)	700 lbs (320 kg)	700 lbs (320 kg)	Not available	Not Available
Upper Boom Articulation			210°			
Lower Boom Articulation	101°	125°	101°	125°	101°	125°
Stowed Travel Height			11' (3.4 m)			
Maximum Jib Capacity			2000 lbs (900 kg)			
Lower Boom Lift Eye Capacity			2500 lbs (1100 kg)			
Hydraulic System Pressure			3000 psi (210 kg/cm <sup>2</sup> )			
Hydraulic System Type			Open Center			
Upper Boom Insulation Gap	9.5' (2.9 m)	9.5' (2.9 m)	12' (3.7 m)	12' (3.7 m)	14.5' (4.4 m)	14.5' (4.4 m)
Lower Boom Insulation Gap	12" (30 cm)	12" (30 cm)	24" (60 cm)	24" (60 cm)	24" (60 cm)	24" (60 cm)
Approximate Weight of Lift with Pedestal	7230 lbs (3280 kg)	7560 lbs (3430 kg)	7380 lbs (3350 kg)	7710 lbs (3500 kg)	7570 lbs (3430 kg)	7910 lbs (3590 kg)

**Notes**

- All height dimensions are based on a 40" (1.02 m) chassis frame height and a standard 40" (1.02 m) tall pedestal. Subtract 6" (15 cm) for the 36" (.91 m) pedestal. Add 6" (15 cm) for the 46" (1.17 m) pedestal.
- Actual travel height will vary with frame height, cab height, pedestal height, mounting location, etc.



P.O. Box 20368  
Waco, TX 76702-0368  
www.VERSALIFT.com

254.399.2100  
Fax: 254.399.2651  
1-800-825.1085

**TOME**  
MANUFACTURING COMPANY